

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 1 of 1

PATENT NO. : 7,113,371
APPLICATION NO.: 10/080,849
ISSUE DATE : September 26, 2006
INVENTOR(S) : Aaron J. Hanna et al.

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Col. 10, Line 37: After "second" delete "binge" and insert --hinge--.
(Claim 5, Line 17)

Col. 12, Line 29: After "The" delete "bead" and insert --head--.
(Claim 29, Line 1)

MAILING ADDRESS OF SENDER (Please do not use customer number below):

WESTERN DIGITAL TECHNOLOGIES, INC.
Attn: Intellectual Property Dept.
20511 Lake Forest Drive
Lake Forest, CA 92630

This collection of information is required by 37 CFR 1.322, 1.323, and 1.324. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1.0 hour to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: **Attention Certificate of Corrections Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

EXHIBIT A




RECEIVED
CENTRAL FAX CENTER

JUL 12 2006

Western Digital Corporation
20911 Lake Forest Drive, E119-G
Lake Forest, California 92630

Tel: 949.872.7000
Fax: 949.872.6604

TO: COMMISSIONER FOR PATENTS, U.S. PATENT & TRADEMARK OFFICE	
FAX NO: (571) 273-8300 (GENERAL/MAIN FAX LINE)	
NO. OF PAGES: Cover + 14	
CERTIFICATE OF FACSIMILE TRANSMISSION I hereby certify that this correspondence is being facsimile transmitted to the U.S. Patent and Trademark Office on the date indicated below. Sandra Genua Typed/Printed Name  Signature July 12, 2006 Date	APPLICATION NO.
	10/080,849
	FILING DATE
	02/22/2002
	FIRST NAMED INVENTOR
	Hanna, et al.
	ART UNIT
2627	
CONFIRMATION NO.	9641
EXAMINER	MAGEE, Christopher R.
ATTORNEY DOCKET NO.	A1056
TITLE	SUSPENSION DESIGN FOR ATTENUATION OF DISK FLUTTER INDUCED TRACK MIS-REGISTRATION OF A HARD DISK DRIVE BY MANIPULATION OF THE HINGE AND/OR LOAD BEAM

ATTACHED WITH THIS SUBMISSION:

1. Fax transmittal Cover Sheet (this page)
2. Response to Office Action dated 06/20/2006 (14 pages)

PLEASE CONFIRM RECEIPT OF THIS TRANSMISSION. IF THERE IS ANY PROBLEM WITH THIS TRANSMISSION, PLEASE CALL SANDRA GENUA AT (949) 672-7780.

CONFIDENTIALITY NOTE

THE INFORMATION CONTAINED IN THIS FACSIMILE TRANSMISSION MAY BE LEGALLY PRIVILEGED AND IS CONFIDENTIAL INFORMATION INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IT IS EXEMPT FROM DISCLOSURE UNDER APPLICABLE LAW, INCLUDING COURT ORDERS, IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT OR THE EMPLOYEE OR AGENT RESPONSIBLE FOR DELIVERING THIS FACSIMILE TRANSMISSION TO THE INTENDED RECIPIENT. YOU ARE HEREBY NOTIFIED THAT ANY USE, DISSEMINATION, DISTRIBUTION OR COPY OF THIS FACSIMILE TRANSMISSION OR ITS INFORMATION IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS FACSIMILE TRANSMISSION IN ERROR, PLEASE IMMEDIATELY NOTIFY US BY TELEFAX OR TELEPHONE USING THE ABOVE NUMBERS AND AIRMAIL THIS FACSIMILE TRANSMISSION BACK TO US IMMEDIATELY. THANK YOU.

V:\IPD\PROGRAM_K31A\FILES\A1000-A\059A1036\PTDA1056_Faxcover_USPTO_071205.doc

JUL 12 2006

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of)	Examiner: Christopher R. MAGEE
Aaron J. HANNA)	Art Unit: 2627
For: SUSPENSION DESIGN FOR)	Confirmation No.: 9641
ATTENUATION OF DISK FLUTTER)	Total Pages: 14
INDUCED TRACK MIS-)	
REGISTRATION OF A HARD DISK)	
DRIVE BY MANIPULATION OF THE)	
HINGE AND/OR LOAD BEAM)	
Serial No.: 10/080,849)	
Filed: February 22, 2002)	
Docket No.: K35A1056)	

RESPONSE TO OFFICE ACTION DATED 06/20/2006

MAIL STOP AMENDMENT
Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

Dear Sir:

The present paper is responsive to the non-final Office Action mailed June 20, 2006.

A complete listing of the Claims begins on page 2 of this paper.

Remarks begin on page 14 of this paper.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

IN THE CLAIMS:

1 - 4. (Cancelled)

5. (Currently Amended) The head stack assembly of Claim 1; A head stack assembly for a disk drive having a disk, the head stack assembly comprising:

a body portion;

an actuator arm cantilevered from the body portion;

a hinge, a first surface of the hinge being coupled to the actuator arm;

a load beam having a first end and a second end, the first end including a load beam surface that faces and contacts a second surface of the hinge, the second surface facing away from the first surface;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal;

wherein the first surface includes

a first convex portion defining a first radius of curvature, adjacent the actuator arm, and adjacent

a first concave portion of the first surface, defining a second radius of curvature , adjacent,

a second convex portion of the first surface, defining a third radius of curvature, adjacent

a second concave portion of the first surface, adjacent the first end.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

6 - 8. (Cancelled)

9. (Currently amended) ~~The disk drive of Claim 6;~~ A disk drive, comprising:

a disk having a recording surface;

a head stack assembly, including:

a body portion;

an actuator arm cantilevered from the body portion;

a hinge, a first surface of the hinge being coupled to the actuator arm;

a load beam having a first end and a second end, the first end including a load beam surface that faces and contacts a second surface of the hinge, the second surface facing away from the first surface;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal;

wherein the first surface includes

a first convex portion defining a first radius of curvature, adjacent the actuator arm, and adjacent

a first concave portion of the first surface, defining a second radius of curvature, adjacent,

a second convex portion of the first surface, defining a third radius of curvature, adjacent

a second concave portion of the first surface, adjacent the first end.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

10. (Previously presented) The disk drive of Claim 9, wherein the third radius is greater than the second radius.

11-13. (Cancelled)

14. (Currently amended) The head gimbal assembly of Claim 11, A head gimbal assembly for a head stack assembly of a disk drive, comprising:

a hinge having a first hinge surface and a second hinge surface;

a mount plate coupled to the first hinge surface;

a load beam having a first end and a second end, the first end including a load beam surface that faces and contacts the second hinge surface, the second hinge surface facing away from the first hinge surface;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal;

wherein the hinge includes a radius geometry that defines a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

15. (Previously presented) A suspension for a head stack assembly of a disk drive, the suspension comprising:

a hinge, having a first hinge end and a second hinge end;

a mount plate coupled to the first hinge end;

a load beam having a first load beam end and a second load beam end, the first load beam end being coupled to the second hinge end; and

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

a gimbal coupled to the second load beam end;

the hinge including a first surface having

a first convex portion defining a first radius of curvature, adjacent the first hinge end, and adjacent

a first concave portion of the first surface, defining a second radius of curvature, adjacent,

a second convex portion of the first surface, defining a third radius of curvature, adjacent

a second concave portion of the first surface, adjacent the second hinge end.

16. (Original) The suspension of Claim 15, wherein the hinge has a thickness that is greater than 0.05 mm.

17. (Original) The suspension of Claim 15, wherein the load beam has a thickness that is greater than 0.12 mm.

18. (Previously presented) The suspension of Claim 15, wherein the third radius is greater than the second radius.

19. (Previously presented) The suspension of claim 15, wherein the first surface is coupled to the mount plate.

20. (Previously presented) The suspension of Claim 19, wherein the hinge further comprises a second surface opposing the first surface and the second surface faces and is in contact with a surface of the load beam.

21. (Original) The suspension of Claim 19, wherein the load beam has a thickness that is greater than 0.12 mm.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

22. (Previously presented) The suspension of Claim 19, wherein the first radius is closer to the mount plate than the second radius, the second radius is closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

23. (Previously presented) A head gimbal assembly for a head stack assembly of a disk drive, the head stack assembly including a body portion, an actuator arm cantilevered from the body portion, the disk drive having a disk, the head gimbal assembly comprising:

a load beam having a first end and a second end, the first end defining an integral hinge portion, the hinge portion defining a radius geometry that includes at least three radii of curvatures configured to lower load beam toward the disk such that a first surface of the hinge portion defines at least two concave portions and at least two convex portions, the first surface of the hinge portion being coupled to the actuator arm;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal.

24. (Previously presented) The head gimbal assembly of Claim 23, wherein the hinge portion has a thickness that is greater than 0.05 mm.

25. (Original) The head gimbal assembly of Claim 23, wherein the load beam has a thickness that is greater than 0.12 mm.

26. (Original) The head gimbal assembly of Claim 23, wherein the radius geometry includes a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

27. (Previously presented) A head stack assembly for a disk drive having a disk, the head stack assembly comprising:

a body portion;

an actuator arm cantilevered from the body portion;

a load beam having a first end and a second end, the first end defining an integral hinge portion, the hinge portion defining a radius geometry that includes at least three radii of curvatures configured to lower load beam toward the disk such that a first surface of the hinge portion defines at least two concave portions and at least two convex portions, the first surface of the hinge portion being coupled to the actuator arm;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal.

28. (Previously presented) The head stack assembly of Claim 26, further including a mount plate attached to the actuator arm, the hinge portion being coupled to the actuator arm via the mount plate, the mount plate having a thickness that is greater than 0.22 mm.

29. (Previously presented) The head stack assembly of Claim 27, wherein the hinge portion has a thickness that is greater than 0.05 mm.

30. (Original) The head stack assembly of Claim 27, wherein the load beam has a thickness that is greater than 0.12 mm.

31. (Original) The head stack assembly of Claim 27, wherein the radius geometry includes a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

32. (Previously presented) A disk drive, comprising:

a disk having a recording surface;

a head stack assembly, including:

a body portion;

an actuator arm cantilevered from the body portion;

a load beam having a first end and a second end, the first end defining an integral hinge portion, the hinge portion defining a radius geometry that includes at least three radii of curvatures configured to lower load beam toward the disk such that a first surface of the hinge portion defines at least two concave portions and at least two convex portions, the first surface of the hinge portion being coupled to the actuator arm;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal.

33. (Previously presented) The disk drive of Claim 32, further including a mount plate attached to the actuator arm, the hinge portion being coupled to the actuator arm via the mount plate, the mount plate having a thickness that is greater than 0.22 mm.

34. (Previously presented) The disk drive of Claim 32, wherein the hinge portion has a thickness that is greater than 0.05 mm.

35. (Original) The disk drive of Claim 32, wherein the load beam has a thickness that is greater than 0.12 mm.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

36. (Original) The disk drive of Claim 32, wherein the radius geometry includes a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

37. (Previously presented) A head stack assembly for a disk drive having a disk, the head stack assembly comprising:

a body portion;

an actuator arm cantilevered from the body portion;

a hinge defining a radius geometry, the radius geometry including at least three radii of curvatures such that a first surface of the hinge defines at least two concave portions and at least two convex portions, the hinge being coupled to the actuator arm;

a load beam having a first end and a second end, the first end being coupled to the hinge;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal.

38. (Original) The head stack assembly of Claim 37, further including a mount plate attached to the actuator arm, the hinge being coupled to the actuator arm via the mount plate, the mount plate having a thickness that is greater than 0.22 mm.

39. (Previously presented) The head stack assembly of Claim 37, wherein the hinge further comprises a second surface opposing the first surface and the second surface faces and is in contact with a surface of the load beam.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

40. (Previously presented) The head stack assembly of Claim 37, wherein the first surface faces and is in contact with a surface of the load beam.

41. (Original) The head stack assembly of Claim 37, wherein the radius geometry includes a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

42. (Previously presented) A disk drive, comprising:

a disk having a recording surface;

a head stack assembly, including:

a body portion;

an actuator arm cantilevered from the body portion;

a hinge defining a radius geometry, the radius geometry including at least three radii of curvatures such that a first surface of the hinge defines at least two concave portions and at least two convex portions, the hinge being coupled to the actuator arm;

a load beam having a first end and a second end, the first end being coupled to the hinge;

a gimbal coupled to the second end of the load beam, and

a slider coupled to the gimbal.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

43. (Original) The disk drive of Claim 42, further including a mount plate attached to the actuator arm, the hinge being coupled to the actuator arm via the mount plate, the mount plate having a thickness that is greater than 0.22 mm.

44. (Previously presented) The disk drive of Claim 42, wherein the hinge further comprises a second surface opposing the first surface and the second surface faces and is in contact with a surface of the load beam.

45. (Previously presented) The disk drive of Claim 42, wherein the first surface faces and is in contact with a surface of the load beam.

46. (Original) The disk drive of Claim 42, wherein the radius geometry includes a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

47. (Previously presented) A head gimbal assembly for a head stack assembly of a disk drive, the head stack assembly including a body portion, an actuator arm cantilevered from the body portion, the disk drive having a disk, the head gimbal assembly comprising:

a hinge defining a radius geometry, the radius geometry including at least three radii of curvatures such that a first surface of the hinge defines at least two concave portions and at least two convex portions, the hinge being coupled to the actuator arm;

a load beam having a first end and a second end, the first end being coupled to the hinge;

a gimbal coupled to the second end of the load beam, and

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

a slider coupled to the gimbal.

48. (Previously presented) The head gimbal assembly of Claim 47, wherein the hinge further comprises a second surface opposing the first surface and the second surface faces and is in contact with a surface of the load beam.

49. (Previously presented) The head gimbal assembly of Claim 47, wherein the first surface faces and is in contact with a surface of the load beam.

50. (Original) The head gimbal assembly of Claim 47, wherein the radius geometry includes a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

51. (Previously presented) A suspension for a head stack assembly of a disk drive, the suspension comprising:

a hinge defining a radius geometry, the radius geometry including at least three radii of curvatures such that a first surface of the hinge defines at least two concave portions and at least two convex portions;

a mount plate coupled to the first surface;

a load beam having a first end and a second end, the first end being coupled to the hinge,
and

a gimbal coupled to the second end of the load beam.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

52. (Original) The suspension of Claim 51, wherein the hinge has a thickness that is greater than 0.05 mm.

53. (Original) The suspension of Claim 51, wherein the load beam has a thickness that is greater than 0.12 mm.

54. (Original) The suspension of Claim 51, wherein the radius geometry includes a first radius of curvature, a second radius of curvature and a third radius of curvature, the first radius being closer to the mount plate than the second radius, the second radius being closer to the mount plate than the third radius, and wherein the third radius is greater than the second radius.

Art Unit 2653
Serial No. 10/080,849

PATENT
Attorney Docket No.: K35A1056

REMARKS


In the non-final Office Action mailed June 20, 2006, claims 1-4, 6-8, and 11-13 were rejected, claims 15-54 were allowed, and claims 5, 9, 10, and 14 were objected to as being dependent upon a rejected base claim. The examiner indicated that claims 5, 9, 10, and 14 would be allowable if re-written in independent form including all of the limitations of the base claim and any intervening claims.

Accordingly, and to quickly advance this case to allowance, Applicants have hereby cancelled all of the rejected claims and have re-written claims 5, 9, 10, and 14 in independent form including all of the limitations of the base claim and any intervening claims.

Applicants respectfully submit that all remaining claims are now in condition for allowance. If it is believed that a telephone conversation would expedite the prosecution of the present application, or clarify matters with regard to its allowance, the Examiner is invited to contact the undersigned attorney at the number listed below. The Commissioner is authorized to charge any fees which may be required to Deposit Account 23-1209.

Respectfully submitted,

Date: July 12, 2006

By: 
Joshua C. Harrison, Ph.D., Esq.
(Registration No. 45,686)

Western Digital Corporation
20511 Lake Forest Drive
Lake Forest, CA 92630
Tel.: (949) 672-6119
Fax: (949) 672-6604

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Appln. of: Aaron J. Hanna, et al.

Patent No.: 7,113,371

Issue Date: 9/26/2006

For: SUSPENSION DESIGN FOR
ATTENUATION OF DISK FLUTTER
INDUCED TRACK MIS-REGISTRATION
OF A HARD DISK DRIVE BY
MANIPULATION OF THE HINGE AND/OR
LOAD BEAM

Serial No.: 10/080,849

Filing Date: 2/22/2002

Examiner: Angel Castro

Docket No.: A1056

**REQUEST FOR CERTIFICATE OF CORRECTION
PURSUANT TO 35 U.S.C. § 254**

ATTN: Certificate of Correction Branch
Commissioner for Patents
P.O. Box 1450
Arlington, VA 22313-1450

Dear Sir/Madam:

The following errors were noted in the above-referenced patent. Applicant hereby requests that the Commissioner issue a Certificate of Correction, without charge.

In the Claims:

Column 10, Line 37:

After "second", please delete "binge" and insert --hinge--. Attached as Exhibit A is a copy of the amendment filed July 12, 2006 which shows the correct wording of Claim 5, renumbered in the issued patent as Claim 1.

Column 12, Line 29:

After "The", please delete "bead" and insert --head--. Attached as Exhibit A is a copy of the amendment filed July 12, 2006 which shows the correct wording of Claim 39, renumbered in the issued patent as Claim 29.

A Certificate of Correction (PTO/SB/44) is enclosed. No fee is believed to be due. However, the Commissioner is hereby authorized to charge payment of any required fees associated with this communication or credit any overpayment to Deposit Account No. 23-1209.

Respectfully submitted,

Date: March 4, 2008

By: /Stacey A. Mollohan/
Stacey A. Mollohan, Esq.
Reg. No. 48,257

WESTERN DIGITAL TECHNOLOGIES, INC.
20511 Lake Forest Drive
Lake Forest, CA 92630
Tel.: (949) 672-7000
Fax: (949) 672-6604